

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (previously presented) A method of charging a battery, comprising the steps of:
receiving an input power supply signal that is used to charge a battery,
wherein the input power supply signal continues to fluctuate after its receipt;
monitoring a voltage level of the input power supply signal to determine when
the fluctuating input power supply signal reaches first and second predetermined
thresholds; and
in response to said monitoring step, selectively controlling a charging switch
that controls the flow of the input power supply signal to the battery, wherein said
controlling step comprises activating the switch when the voltage level of the input power
supply signal increases to reach the first predetermined threshold and deactivating the
switch when the voltage level of the input power supply signal decreases to reach the
second predetermined threshold.
2. (previously presented) The method according to claim 1, further comprising
maintaining, through a capacitor, the voltage level of the input power supply signal to
indicate that the electronic device is being charged.

3. (original) The method according to claim 1, further comprising the step of synchronizing with said controlling of the charging switch the control of a second switch that regulates current flow to a circuit such that the second switch to the circuit is activated when the charging switch is activated and deactivated when the charging switch is deactivated.
4. (previously presented) The method according to claim 3, wherein the synchronizing step further comprises synchronizing with said controlling of the charging switch the control of the second switch that regulates current flow to a backlighting circuit such that the second switch to the backlighting circuit is activated when the charging switch is activated and deactivated when the charging switch is deactivated.
5. (original) The method according to claim 1, further comprising the step of performing said receiving, monitoring and controlling steps in a wireless charging system.
6. (original) The method according to claim 1, further comprising the step of rectifying the input power supply signal.
7. (previously presented) The method according to claim 1, wherein the magnitude of the second predetermined threshold is lower than the magnitude of the first predetermined threshold.

8. (previously presented) A method of charging a battery, comprising the steps of:

receiving an input power supply signal in an electronic device having a capacitor with a value high enough to maintain a voltage level of the input power supply signal to indicate that the electronic device is being charged to prevent disabling of a charging sequence for the battery;

monitoring the voltage level of the input power supply signal to determine when the voltage level of the input power supply signal reaches first and second predetermined thresholds;

selectively controlling a charging switch that controls the flow of the input power supply signal to the battery, wherein said controlling step comprises activating the switch when the voltage level of the input power supply signal increases to reach the first predetermined threshold and deactivating the switch when the voltage level of the input power supply signal decreases to reach the second predetermined threshold, wherein the magnitude of the second predetermined threshold is lower than the magnitude of the first predetermined threshold.

9. (previously presented) A charging system for charging a battery, comprising:
- an input for receiving an input power supply signal, wherein the input power supply signal continues to fluctuate after the input receives the input power supply signal;
 - a charging switch for controlling the flow of said input power supply signal to said battery; and
 - a controller, wherein said controller is operable to:
 - monitor a voltage level of said fluctuating input power supply signal to determine when the voltage level of said input power supply signal reaches first and second predetermined thresholds; and
 - in response to the monitoring process, selectively control said charging switch by activating said charging switch when the voltage level of said input power supply signal increases to reach said first predetermined threshold and by deactivating said switch when the voltage level of said input power supply signal decreases to reach said second predetermined threshold.
10. (previously presented) The charging system according to claim 9, further comprising a capacitor that maintains the voltage level of the input power supply signal that said controller monitors to determine that said battery is being charged.

11. (original) The charging system according to claim 9, further comprising a circuit and a second switch that regulates current flow to said circuit, said second switch being under the control of said controller, wherein said controller is further programmed to synchronize with the controlling of said charging switch the control of said second switch such that said controller activates said second switch when said charging switch is activated and disables said second switch when said charging switch is deactivated.
12. (original) The method according to claim 11, wherein said circuit is a backlighting circuit.
13. (original) The charging system according to claim 9, wherein said charging system is a wireless charging system.
14. (original) The charging system according to claim 9, further comprising a rectifier, wherein said rectifier rectifies said input power supply signal.
15. (previously presented) The charging system according to claim 9, wherein the magnitude of said second predetermined threshold is lower than the magnitude of said first predetermined threshold.